

Proper Care and Use of EZ2CY®

Waxing:

If desired, wax EZ2CY® with a good quality auto paste wax. (Avoid waxes with color.) Follow by wiping with a damp cloth to remove static.

Scratches:

Most scratches can be removed by hand polishing with compounds such as Simoniz cleaner or Finishes®. Use of electric buffer may facilitate; keep moving over area, use light pressure, keep area moist using spray bottle with clean water. Rinse and follow with an acrylic safe Cleaner/Polish.

DO NOT USE:

Window cleaning sprays, RAINEX®, Kitchen Scouring Compounds, solvents such as Acetone, Lacquer Thinner or cleaners that contain alcohol, any form of lubricant. CAUTION needs to be exercised when using metal cleaner on pipe work that is adjacent to the enclosure!

Removing Panels from Boat

EZ2CY® enclosures are designed to remain on the boat. The probability of scratching or damaging a panel in the process of removing or replacing far outweighs any benefit of storage. If panels must be removed, contact an EZ2CY® dealer near you.

Up to date information is available at

www.EZ2CY.com

www.EZ2CY.com • 800-448-4317 • www.EZ2CY.com • 800-448-4317 • www.EZ2CY.com

Enclosures

EZ2CY®

EZ2CY®

Enclosures

Congratulations:

You have purchased an EZ2CY® crystal clear enclosure. With the proper care, your EZ2CY® enclosure will last for many years and afford you the pleasure of safe, distortion free boating. The EZ2CY® dealers would like for your experience with our product and services to be favorable. Our collective goal is to make it easy to see why you will choose us for your next vessel and recommend us to all of your yachting friends. This is why we have EZ2CY® dealers located around the world and pride ourselves in consistent quality, no matter which EZ2CY® dealer you visit.

This pamphlet will attempt to answer any questions that may arise while enjoying your new EZ2CY® enclosure, but if you should have additional questions and/or comments please visit us at www.EZ2CY.com or call us at 800-448-4317. We will be more than happy to address your concerns.

Proper Care and

Use of EZ2CY®

Initial Care:

Initial and occasional use of EZ2CY® Enclosure Cleaner/Polish removes static that attracts dust and makes future washing easier. This product is easy to use and has anti-fog properties as well as helping to shed water. Use of Bounty® paper towels are suggested for this procedure since it is soft, absorbent and leaves little to no residue behind.

Normal Washing:

Use the salt off your enclosure with fresh water after each day of use and periodically when exposed to salt air. More extensive cleaning may be accomplished with the use of common household cleansers in conjunction with a soft mitt reserved for use in conjunction with a fresh water rinse. A soft brush may also be used if so desired. A squeegee or water blade, having no sharp edges, may also be used if so desired.

Zipper Care:

Slipping and washing of zippers with soap and water followed by a thorough rinsing of fresh water is recommended. If zipper tape is especially dirty, use a light solution of wool-light type detergent followed by a thorough rinsing with fresh water. **DO NOT USE ANY FORM OF LUBRICANT!**

Opening and Closing Panels:

Open only those panels designed to be opened. At time of installation your dealer will demonstrate and give specific instructions for opening and closing your EZ2CY® enclosure. Some general rules apply to all opening panels:

When opening or closing an EZ2CY® panel caution should be taken to prevent excessive bending. When handling panels the wind can be an important factor. If under way-reduce boat speed. Turn boat if required to eliminate excess wind. Vertical zippers must be open to the top track. (Sliding panels: fully open and separate zippers) Hold panel with one hand while unzipping bottom zipper. This will give you control of the panel. Pull panel in and up to top; fasten appropriately. (Sliding panels: slide panel and fasten appropriately) If panels are rubbing on each other, insert a paper towel, clear suction cup or similar soft product to prevent scratching.

EZ2CY® Enclosure Limited Warranty

What is Covered: This warranty covers clarity of enclosure (not to change light transmission by more than 3% in five years) and strength and fading in fabric and thread.

Length of Coverage: This warranty is pro-rated to last for five years. (100% first year, 80% second year, 60% third year, 40% fourth year and 20% fifth year)

What EZ2CY® will do: EZ2CY® will repair or replace any defective piece at no charge. The cost for removing and reinstalling, travel or shipping and handling will be your sole responsibility.

What is Not Covered: Any problem that is caused by abuse, misuse, negligence, improper care or an act of God. See "Proper Care and Use of EZ2CY®"

Where to get Service: In order to be eligible for service under this warranty you **MUST** return the warranty registration or fill out the warranty registration online at www.EZ2CY.com within 30 days after installation of enclosure.

Contact any licensed EZ2CY® dealer listed on our website at www.EZ2CY.com or contact us at 800-448-4317.

State Law: This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Online registration:
www.EZ2CY.com

This warranty applies under conditions of normal usage and does not apply to any acts of God or failure resulting from negligence or misuse. See "Proper Care and Use of EZ2CY®." EZ2CY® retains the option to repair or replace the defective panel. Cost for travel or packing and shipping is not covered by this warranty. Repair/replacement of enclosure as covered by this warranty is pro-rated on a 5 year basis, i.e., 100% first year, 80% second year, 60% third year, 40% fourth year, and 20% fifth year. These percentages are based on prevailing retail costs.